



OBMW2.E194410 Magnet Wire - Component

Page Bottom

Magnet Wire - Component

See General Information for Magnet Wire - Component

SHANDONG SAINT ELECTRIC CO LTD

E194410

YUNSHAN RD

HIGH-TECH DEVELOPING ZONE


XINTAI, SHANDONG 271200 CHINA

Material Designation	Mark Dsg	Base Coat	Top Coat	ANSI Type	Temp Class
EI/AIW, Q(ZY/XY)	EI/AIW, Q(ZY/XY)	Polyester-imide	Polyamide-imide	MW 35-A	220
		Polyester-imide	Polyamide-imide	MW 37-C	220
		Polyester-imide	Polyamide-imide	MW 73-A	220
		Polyester-imide	Polyamide-imide	MW 35-C	200[#]
		Polyester-imide	Polyamide-imide	MW 73-C	200[#]
EIW	EIW	Polyester-imide	-	MW 30-C	180
EIW/AI	EIW/AI	Polyester-imide	Polyamide-imide	MW 35-C	200
PEW N/155	PEW N/155	Polyester	Polyamide	MW 24-C	155[#]
PEW N/180	PEW N/180	Polyester	Polyamide	MW 76-C	180
PEW, QZ	PEW, QZ	Polyester-imide	-	MW 74-C	200[#]
		Polyester-imide	-	MW 30-C	180[#]
		Modified Polyester	-	MW 5-C	155[#]
UEW N/130, QA N/130, UEW N/130 Litz, QA N/130 Litz	UEW N/130, QA N/130, UEW N/130 Litz, QA N/130 Litz	Polyurethane	Polyamide	MW 28-C	130[#]
UEW N/155	UEW N/155	Polyurethane	Polyamide	MW 80-C	155
		Polyurethane	Polyamide	MW 28-C	130[#]
UEW N/155, QA N/155, UEW N/155 Litz, QA N/155 Litz	UEW N/155, QA N/155, UEW N/155 Litz, QA N/155 Litz	Polyurethane	Polyamide	MW 80-C	155[#]
UEW N/180, QA N/180, UEW N/180 Litz, QA N/180 Litz	UEW N/180, QA N/180, UEW N/180 Litz, QA N/180 Litz	Polyurethane	Polyamide	MW 83-C	180
UEW, QA	UEW, QA	Polyurethane	-	MW	155

					79-C	
UEW/130, QA/130, UEW/130 Litz, QA/130 Litz	UEW/130, QA/130, UEW/130 Litz, QA/130 Litz	Polyurethane	-		MW 75-C	130[#]
UEW/155, QA/155, UEW/155 Litz, QA/155 Litz	UEW/155, QA/155, UEW/155 Litz, QA/155 Litz	Polyurethane	-		MW 79-C	155[#]
UEW/180, QA/180, UEW/180 Litz, QA/180 Litz	UEW/180, QA/180, UEW/180 Litz, QA/180 Litz	Polyurethane	-		MW 82-C	180

Material Designation	Mark Dsg	Base Coat	Top Coat	Bond Coat	ANSI/Conductor Type	Temp Class
PEW N/130	PEW N/130	Polyester	Polyamide	-	-	130[#]

[#] - The magnet wire may perform better than the rating reflects and may not be suitable for insulation system, varnish or end-product testing. Further consideration is necessary prior to its use in testing.

Marking: Company name, material designation or marked designation and the Recognized Component Mark,  on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2014-03-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".